



Mechanized Tunnelling in Urban Areas

Design Methodology and Construction Control

Edited by
Vittorio Guglielmetti
Piergiorgio Grasso
Ashraf Mahtab
Shulin Xu
Geodata S.p.A., Turin, Italy



CRC Press is an imprint of the
Taylor & Francis Group, an **informa** business
A TAYLOR & FRANCIS BOOK

Contents

<i>Contributors</i>	ix
<i>Preface</i>	xi
<i>Executive summary</i>	xv
1 Introduction: tunnels in urban areas and the related challenges	1
1.1 The opportunities	1
1.2 The particular challenges of urban tunnelling	4
1.3 The correct approach to success	5
1.4 A brief history of mechanized tunnelling	8
1.5 The scope of this book	13
2 Initial risks: definition, analysis and management	19
2.1 Basic definitions	20
2.2 Sources of initial risk in mechanized urban tunnelling	21
2.3 Analysis and management of risks: the risk management plan	22
2.4 Designing for the identified risk scenario	35
2.5 Quantifying the risk of time and cost overruns at the design stage with the use of DAT	42
2.6 Use of Plan for Advance of Tunnel (PAT) for controlling the residual risks	50
3 Selection of tunnel alignment with low-level risks	53
3.1 Introduction	53
3.2 The general layout of an urban tunnel	55

3.3	Alignment constraints and specific functional requirements	56
3.4	Constraints and peculiar characteristics of the urban environment relevant to the selection of a tunnel route	65
3.5	Starting and arrival points, shield launching and receiving shafts, logistic work sites	71
3.6	The relationship between the excavation of running tunnel by TBM and the construction of the stations	73
3.7	Conclusions	74
4	The primary responses to the initial risks: a “city machine” and its essential characteristics	75
4.1	Principles for making the macro choices	75
4.2	The common solution: a “city machine”	78
4.3	Essential components of a “city machine”	79
4.4	Slurry and earth pressure balance shields: functioning principles and review of the state of the art	89
4.5	Some considerations for the choice between HS and EPBS	105
5	Tunnel design	113
5.1	Prediction and control of tunnelling-induced settlements and assessment of their impacts	113
5.2	The design of face-support pressure	152
5.3	The design of precast concrete segmental lining	176
5.4	Backfilling of the tail void	223
6	The control of tunnel construction	235
6.1	Updating and implementation of PAT	235
6.2	Excavation control: the case of slurry/hydro shield (SS/HS)	240
6.3	Excavation control: the case of earth pressure balance shield (EPBS)	254
6.4	Integrated real-time monitoring system	266
7	Health and safety	279
7.1	General considerations	279

7.2	TBM working environment	281
7.3	Critical processes	281
7.4	Additional critical elements	291
7.5	Emergencies	295
8	Case histories	297
8.1	EOLE project – Paris	297
8.2	St. Petersburg metro	305
8.3	Porto light metro	312
8.4	Turin metro line 1	325
8.5	SMART solution of Kuala Lumpur (Malaysia)	337
8.6	High speed railway line of Nodo di Bologna	344
	References	355
	Appendices	363
Appendix 1	Type and characteristics of TBMs	363
Appendix 2	TBM manufacturers from the new millennium	373
Appendix 3	Geotechnical investigations for tunnelling in urban areas	379
Appendix 4	Description of the principal elements of the 12 analytical methods for defining face-support pressure	391
Appendix 5	An example of risk management plan for a job using slurry shield	403
Appendix 6	Typical excavation procedures for EPB shield	413
Appendix 7	The Italian experiences	433
	Annex	
	Contract and construction aspects	461
	Glossary of terms	499
	Index	505