NPSH for rotodynamic pumps: a reference guide

European Association of Pump Manufacturers





Contents

		Page	
Pre	eface		
1.	Introduction 1.1. Importance of inlet conditions 1.2 Cavitation 1.3. Effects of inadequate suction conditio	1 1 1 2	
2.	The concept of NPSH 2.1. Pressure profile along the streamline 2.2. Definition of NPSH 2.3. Practical definition of NPSHR 2.4. Other qualifying criteria for NPSH	5 5 5 8 10	
3.	Governing parameters 3.1. Effect of speed and capacity 3.2. Effect of pump geometry 3.3. Effect of impeller trim 3.4. Effect of pumped liquid 3.5. Effect of inlet piping 3.6. Effect of pump material	13 13 14 15 16 17 18	
4.	Suction specific speed		
5.	Safety margins between NPSHR and NPSHA		
6.	Practical determination of NPSHR 3		

7.	Dete	rmination of NPSHA	33
	7.1.	Atmospheric pressure	34
	7.2.	Reference level	35
	7.3.	Temperature and vapour pressure	36
	7.4.	Velocity head	36
	7.5.	Measurements from Bourdon gauges	36
	7.6.	Conversion from pressure to head	37
8.	Examples of calculation of NPSHA		
	8.1.	The state of the s	20
	0.0	atmospheric pressure	39
	8.2.	Pumps under negative head and liquid under atmospheric pressure	40
	8.3.	Liquid level under positive pressure and pump below the liquid level	41
	8.4.		42
	8.5.		42
	8.6.	Liquid level under negative pressure and pump above the liquid level	44
	8.7.	Liquid level under the vapour pressure of the liquid	45
0	Oth	5 7 Year 10 Aug 10 Aug 17	47
9.		r phenomena Suction recirculation	47
			48
		Corrosion	48
	9.3.	[B : CONTROL OF CONT	49
	9.4.	Air or gas entrainment	50
	9.5.	Dissolved gases	30
10	10. Conclusions		51
11	. Tern	ns, symbols and units	53
Ap	pendi	ces	
		endix A	57 59
	Appendix B		
Appendix C			
	Appendix D		67
	Appe	endix E	71